

Shrink Tunnel / Chamber - Heavy Duty



(Photograph is for the reference purpose only. Machine Construction & Specification are subject to change without prior Notice due to Continues up-gradation Process)

Salient Features of the Equipments

- Easy to operate.
- Virtually low maintenance.
- Low Power Consumption.
- Electronic Digital Temperature Controller.
- High efficiency heaters.
- Suitable for PVC & LDPE films.
- Separate Key System Door.
- Fixed / Variable Conveyer Speed.

Technical Specification of the Equipments

- **Machine Dimension:** 1475 mm (L) x 425 mm (W) x 1150 mm (H)
- **Counter (Window) Size:** 12 inch x 12 inch
- **MOC of Machine:** Machine will be fabricated in CRC sheet in 16 gauges with suitable angle and powder coated body
- **Conveyor:** Heavy Duty chains with pins for conveyor assembly (Diamond make) or Rollers
- **Heaters:** 12 K.W S.S. Tube type heaters with fine Digital Temperature controller with sensor to control the chamber temperature
- **Output Speed:** 20 to 40 Products Per Minute (Depending up on the size of the Products)
- **Conveyor Speed:** Fixed / Variable
- **Temperature:** 70° to 200°
- **Material:** PVC / LDPE
- **Power Load:** Single Phase, + Neutral, 4 KW, 440 V.